



FOR INDUSTRY PROFESSIONALS



# AIR CONDITIONING HARD STARTS

# YOUR HARD START SOURCE.

INCREASE STARTING TORQUE UP TO 500% WITH AN ECONOMIC SOLUTION.

- ✓ Field proven reliability
- ✓ Easy two-wire installation
- ✓ NATE® recognized
- ✓ UL® approved
- ✓ Can be used on PSC type compressors

## Technical Specifications

### TP-5

Torque: 300%  
Capacitor size (μF): 43 to 53 MFD  
Recommended Range (hp): 1/2 - 10 hp  
Operating Voltage VAC: 90 to 277 VAC

### TP-6

Torque: 500%  
Capacitor size (μF): 130 to 156 MFD  
Recommended Range (hp): 1/2 - 10 hp  
Operating Voltage VAC: 90 to 277 VAC

### 2-WIRE

Positive Temperature Coefficient (PTC) Technology

TRADEPRO P/N	INCREASE IN TORQUE
TP-5	300%
TP-6	500%



## 2-WIRE

### Positive Temperature Coefficient (PTC) Technology

TRADEPRO P/N	Packard®	Diversitech®	Mars®
TP-5	HS5	DST-5	32702
TP-6	HS6	DST-6	32701

Packard®, Diversitech®, and Mars® are trademarks of their respective owners. Reasonable effort has been made to assure the accuracy of cross-reference information. However, final evaluation for suitable replacement is left to the installer.