

## TP-V7A2L-USA

7.2 CFM DC Motor Vacuum Pump





## **FEATURES**

- A2L compatible
- 1/2 HP DC motor operates in low voltage situations
- Dual voltage at a flip of a switch (115v/230v)
- IEC 10 ft. locking cord
- Lightweight
- 25 micron vacuum rating
- American-made all metal construction to last a lifetime
- Ergonomic 1/2" break resistant exhaust handle
- · Large, easy-to-see oil level sight glass with easy access oil fill located on cover
- O-ring sealed drain valve
- Tethered safety cap to prevent oil spills
- Field repairable

## **Technical Support**

Contact the Sales Center from where the product was purchased for technical support.

Acme Refrigeration www.acmeref.com (800) 324-1258

Baker www.bakerdist.com (844) 289-0033 **CE USA** 

www.carrierenterprise.com

DASCO Supply www.dascosupply.com

East Coast Metals www.ecmdi.com

Gemaire www.gemaire.com (888) 601-0038 Homans Associates www.homans.com

**N&S Supply** www.nssupply.com (845) 896-6291

## **SPECIFICATIONS**

Models 7.2 CFM

**MOTOR** 

1/2 HP, DC Motor

**INTAKE PORTS** 

1/4" x 3/8" Male

**VOLTAGE** 

Dual-voltage; 115v/230v

**WEIGHT** 

24 lbs

Oil Capacity

25 oz

Peirce Phelps www.peirce.com

www.peirce.com (800) 324-2304

TEC

www.tecmungo.com (708) 418-7900